



SANET ALKASTAR 2x5 I

WM 0712472

Order number: 0712472

Version 6.6

Revision Date 24.01.2023

Print Date 05.02.2023

SECTION 1: Identification of the substance/mixture and of the company/undertaking

1.1 Product identifier

Trade name : SANET ALKASTAR 2x5 I
UFI :

1.2 Relevant identified uses of the substance or mixture and uses advised against

Use of the Substance/Mixture : Cleaning agent
Restricted to professional users.

1.3 Details of the supplier of the safety data sheet

Company : Tana Chemie GmbH
Rheinallee 96
55120 Mainz
Telephone : +49613196403
Telefax : +4961319642414
E-mail address : Produktsicherheit@werner-mertz.com
Responsible/issuing person
Contact person : Product development / product safety

1.4 Emergency telephone number

112
Centru za kontrolu otrovanja u Zagrebu na tel. (01) 2348 342
+49(0)6131-19240

SECTION 2: Hazards identification

2.1 Classification of the substance or mixture

Classification (REGULATION (EC) No 1272/2008)
Not a hazardous substance or mixture.

2.2 Label elements

Labelling (REGULATION (EC) No 1272/2008)
Not a hazardous substance or mixture.

Safety data sheet available on request.

2.3 Other hazards

No information available.

SECTION 3: Composition/information on ingredients

3.2 Mixtures

Chemical nature : Aqueous surfactant solution.

Components

Chemical name	CAS-No.	Classification	Concentration
---------------	---------	----------------	---------------



SANET ALKASTAR 2x5 I

WM 0712472

Order number: 0712472

Version 6.6

Revision Date 24.01.2023

Print Date 05.02.2023

	EC-No. Index-No. Registration number		(% w/w)
ethanol	64-17-5 200-578-6 603-002-00-5 01-2119457610-43	Flam. Liq. 2; H225 Eye Irrit. 2; H319 specific concentration limit Eye Irrit. 2; H319 ≥ 50 %	≥ 2 - < 5
Alcohols, C12-14, ethoxylated, sulfates, sodium salts	68891-38-3 500-234-8 01-2119488639-16	Skin Irrit. 2; H315 Eye Dam. 1; H318 Aquatic Chronic 3; H412 specific concentration limit Eye Irrit. 2; H319 5 - < 10 % Eye Dam. 1; H318 ≥ 10,0 %	≥ 1 - < 2

SECTION 4: First aid measures

4.1 Description of first aid measures

- General advice : No hazards which require special first aid measures.
- If inhaled : Move to fresh air in case of accidental inhalation of dust or fumes from overheating or combustion.
If symptoms persist, call a physician.
- In case of skin contact : Take off contaminated clothing and shoes immediately.
Wash off with soap and plenty of water.
- In case of eye contact : Protect unharmed eye.
If easy to do, remove contact lens, if worn.
Rinse immediately with plenty of water, also under the eyelids, for at least 15 minutes.
- If swallowed : Clean mouth with water and drink afterwards plenty of water.
Do not give milk or alcoholic beverages.
Never give anything by mouth to an unconscious person.

4.2 Most important symptoms and effects, both acute and delayed

- Symptoms : No information available.
- Risks : No information available.

4.3 Indication of any immediate medical attention and special treatment needed

- Treatment : For specialist advice physicians should contact the Poisons Information Service.



SANET ALKASTAR 2x5 I

WM 0712472

Order number: 0712472

Version 6.6

Revision Date 24.01.2023

Print Date 05.02.2023

SECTION 5: Firefighting measures

5.1 Extinguishing media

Suitable extinguishing media : Use extinguishing measures that are appropriate to local circumstances and the surrounding environment.

5.2 Special hazards arising from the substance or mixture

Specific hazards during firefighting : Do not allow run-off from fire fighting to enter drains or water courses.

Hazardous combustion products : No hazardous combustion products are known

5.3 Advice for firefighters

Special protective equipment for firefighters : In the event of fire, wear self-contained breathing apparatus.

Further information : Collect contaminated fire extinguishing water separately. This must not be discharged into drains.
Fire residues and contaminated fire extinguishing water must be disposed of in accordance with local regulations.

SECTION 6: Accidental release measures

6.1 Personal precautions, protective equipment and emergency procedures

Personal precautions : Use personal protective equipment.

6.2 Environmental precautions

Environmental precautions : Try to prevent the material from entering drains or water courses.

6.3 Methods and material for containment and cleaning up

Methods for cleaning up : Neutralise with acid.
Sweep up and shovel.
Wipe up with absorbent material (e.g. cloth, fleece).
Keep in suitable, closed containers for disposal.

6.4 Reference to other sections

For personal protection see section 8., Treat recovered material as described in the section "Disposal considerations"., Refer to section 15 for specific national regulation.

SECTION 7: Handling and storage

7.1 Precautions for safe handling

Advice on safe handling : For personal protection see section 8.
No special handling advice required.

Advice on protection against fire and explosion : Normal measures for preventive fire protection.

Hygiene measures : Wash hands before breaks and at the end of workday.



SANET ALKASTAR 2x5 I

WM 0712472

Order number: 0712472

Version 6.6

Revision Date 24.01.2023

Print Date 05.02.2023

7.2 Conditions for safe storage, including any incompatibilities

- Requirements for storage areas and containers : Keep container tightly closed in a dry and well-ventilated place. Store at room temperature in the original container.
- Advice on common storage : No special restrictions on storage with other products.
- Further information on storage stability : No decomposition if stored and applied as directed. Protect from frost.

7.3 Specific end use(s)

- Specific use(s) : Cleaning agent

SECTION 8: Exposure controls/personal protection

8.1 Control parameters

Contains no substances with occupational exposure limit values.

8.2 Exposure controls

Personal protective equipment

- Eye protection : not required under normal use
- Hand protection
- Material : not required under normal use
- Material : For prolonged or repeated contact use protective gloves. It is suggested the usage of chemical resistant gloves made of butyl rubber or nitrile rubber category III according to EN 374. As alternative, a different type of gloves might be used if, accordingly to the recommendations of the producer, guarantee the same level of protection.
- Remarks : Take note of the information given by the producer concerning permeability and break through times, and of special workplace conditions (mechanical strain, duration of contact).
- Skin and body protection : not required under normal use
- Respiratory protection : not required under normal use

SECTION 9: Physical and chemical properties

9.1 Information on basic physical and chemical properties

- Appearance : liquid
- Colour : red
- Odour : characteristic
- Odour Threshold : No data available
- pH : ca. 11,0, 100 %



SANET ALKASTAR 2x5 I

WM 0712472

Order number: 0712472

Version 6.6

Revision Date 24.01.2023

Print Date 05.02.2023

at 20 °C

Melting point/range	: No data available
Boiling point/boiling range	: No information available.
Flash point	: does not flash
Evaporation rate	: No data available
Flammability (solid, gas)	: No data available
Flammability (liquids)	: No data available
Burning rate	: No data available
Lower explosion limit	: No data available
Upper explosion limit	: No data available
Vapour pressure	: No data available
Relative vapour density	: No data available
Relative density	: No data available
Density	: ca. 1,038 g/cm ³ at 20 °C
Water solubility	: soluble
Solubility in other solvents	: No data available
Partition coefficient: n-octanol/water	: No data available
Ignition temperature	: No data available
Thermal decomposition	: No data available
Viscosity, dynamic	: No data available
Viscosity, kinematic	: No data available
Explosive properties	: No data available
Oxidizing properties	: No data available

9.2 Other information

none

SECTION 10: Stability and reactivity

10.1 Reactivity

Stable under recommended storage conditions.
No dangerous reaction known under conditions of normal use.

10.2 Chemical stability

No decomposition if stored and applied as directed.

10.3 Possibility of hazardous reactions

Hazardous reactions : No hazards to be specially mentioned.

10.4 Conditions to avoid

Conditions to avoid : Protect from frost.



SANET ALKASTAR 2x5 I

WM 0712472

Order number: 0712472

Version 6.6

Revision Date 24.01.2023

Print Date 05.02.2023

10.5 Incompatible materials

Materials to avoid : No data available

10.6 Hazardous decomposition products

No hazardous decomposition products are known.

SECTION 11: Toxicological information

11.1 Information on hazard classes as defined in Regulation (EC) No 1272/2008

Our company is strongly against animal testing.

Our company does not place any orders for animal testing for the finished product or the ingredients.

However, as a result of EU legislation (REACH Regulation), the manufacturers of ingredients or EU importers are obliged to test ingredients with regard to their effects on human health and the environment before they are brought onto the market. Some of the tests made necessary by this took place decades ago.

Acute toxicity

Acute toxicity : Not Rated

Components:

ethanol

ALCOHOL:

Acute oral toxicity : LD50 Oral (Rat): 10.470 mg/kg
Method: OECD Test Guideline 401

LD50 (Rat): 5.000 mg/kg
Method: OECD Test Guideline 401

Acute inhalation toxicity : LC50 (Rat): 51 mg/l
Exposure time: 4 h

Acute dermal toxicity : LD50 Dermal (Rabbit): > 2.000 mg/kg
Method: OECD Test Guideline 402

LD50 Dermal (Rabbit): > 10.000 mg/kg
Method: OECD Test Guideline 402

Alcohols, C12-14, ethoxylated, sulfates, sodium salts

68891-38-3:

Acute oral toxicity : LD50 Oral (Rat): 2.870 mg/kg
Method: OECD Test Guideline 401

LD50 (Rat): 7.400 mg/kg
Method: OECD Test Guideline 401

LD50 (Rat): 2.000 - 5.000 mg/kg
Method: OECD Test Guideline 401

LD50 (Rat): > 2.000 mg/kg

Acute dermal toxicity : LD50 (Rat): > 2.000 mg/kg



SANET ALKASTAR 2x5 I

WM 0712472

Order number: 0712472

Version 6.6

Revision Date 24.01.2023

Print Date 05.02.2023

Method: OECD Test Guideline 402
GLP: yes

Skin corrosion/irritation

Product:

Remarks : According to the classification criteria of the European Union, the product is not considered as being a skin irritant.

Components:

ethanol

ALCOHOL:

Species : Rabbit
Method : OECD Test Guideline 404
Result : No skin irritation

Alcohols, C12-14, ethoxylated, sulfates, sodium salts

68891-38-3:

Species : Rabbit
Assessment : Irritating to skin.
Method : OECD Test Guideline 404

Serious eye damage/eye irritation

Product:

Remarks : According to the classification criteria of the European Union, the product is not considered as being an eye irritant.

Components:

ethanol

ALCOHOL:

Species : Rabbit
Method : OECD Test Guideline 405
Result : Mild eye irritation

Alcohols, C12-14, ethoxylated, sulfates, sodium salts

68891-38-3:

Species : Rabbit
Assessment : Risk of serious damage to eyes.
Method : OECD Test Guideline 405

Respiratory or skin sensitisation

Product:

Remarks : No data available

Components:

ethanol

ALCOHOL:

Result : Not a skin sensitizer.



SANET ALKASTAR 2x5 I

WM 0712472

Order number: 0712472

Version 6.6

Revision Date 24.01.2023

Print Date 05.02.2023

Alcohols, C12-14, ethoxylated, sulfates, sodium salts

68891-38-3:

Result : Does not cause skin sensitisation.

Germ cell mutagenicity

Germ cell mutagenicity : Not Rated

Components:

Alcohols, C12-14, ethoxylated, sulfates, sodium salts

68891-38-3:

Genotoxicity in vitro : Method: OECD Test Guideline 471
Result: negative

Carcinogenicity : Not Rated

Reproductive toxicity : Not Rated

STOT - single exposure : The substance or mixture is not classified as specific target organ toxicant, single exposure.

STOT - repeated exposure : The substance or mixture is not classified as specific target organ toxicant, repeated exposure.

Repeated dose toxicity

Components:

ethanol

ALCOHOL:

Species : Rat, male
NOAEL : > 20 mg/kg
Method : OECD Test Guideline 403

Species : Rat, female
NOAEL : 1.730 mg/kg
Method : OECD Test Guideline 408

Aspiration toxicity : Not Rated

11.2 Information on other hazards

Further information

Product:

Remarks : No data available



SANET ALKASTAR 2x5 I

WM 0712472

Order number: 0712472

Version 6.6

Revision Date 24.01.2023

Print Date 05.02.2023

SECTION 12: Ecological information

12.1 Toxicity

Components:

ALCOHOL:

- Toxicity to fish : LC50 (Oncorhynchus mykiss (rainbow trout)): 13 g/l
Exposure time: 96 h
Method: OECD Test Guideline 203
- LC50 (Leuciscus idus (Golden orfe)): 8.150 mg/l
Exposure time: 48 h
- LC50 (Pimephales promelas (fathead minnow)): > 0,1 g/l
Exposure time: 96 h
- LC50 (Fish): 11.200 mg/l
- Toxicity to daphnia and other aquatic invertebrates : EC50 (Daphnia magna (Water flea)): 12.340 mg/l
Exposure time: 48 h
- EC50 : 5.012 mg/l
- Toxicity to algae/aquatic plants : EC50 (Chlorella vulgaris (Fresh water algae)): 275 mg/l
Exposure time: 72 h
Test Type: Growth inhibition
Method: OECD Test Guideline 201
- EC50 (Scenedesmus capricornutum (fresh water algae)): 12.900 mg/l
Exposure time: 48 h
Test Type: Growth inhibition
Method: No information available.
- EC0 (Scenedesmus quadricauda (Green algae)): 5.000 mg/l
Exposure time: 168 h
- EC50 : 4.432 mg/l
- EC10 : 11,5 mg/l
- EC10 : 280 mg/l
- Toxicity to microorganisms : EC50 (Pseudomonas putida): 11.800 mg/l
Exposure time: 16 h
Test Type: Cell multiplication inhibition test
- 68891-38-3:**
- Toxicity to fish : LC50 (Danio rerio (zebra fish)): 7,1 mg/l
Exposure time: 96 h
Test Type: flow-through test
Method: OECD Test Guideline 203



SANET ALKASTAR 2x5 I

WM 0712472

Order number: 0712472

Version 6.6

Revision Date 24.01.2023

Print Date 05.02.2023

GLP: yes

LC50 (Fish): > 1 - 10 mg/l
Test Type: semi-static test
Method: OECD Test Guideline 203

LC50 (Leuciscus idus (Golden orfe)): 10 - 100 mg/l
Method: OECD Test Guideline 203

NOEC (Oncorhynchus mykiss (rainbow trout)): 0,14 mg/l
Exposure time: 28 d
Test Type: flow-through test
Method: OECD Test Guideline 204

LC50 (Brachydanio rerio (zebrafish)): 1 - 10 mg/l
Test Type: flow-through test
Method: OECD Test Guideline 203

LC50 (Brachydanio rerio (zebrafish)): 7,1 mg/l
Exposure time: 96 h

Toxicity to daphnia and other aquatic invertebrates : EC50 (Daphnia pulex (Water flea)): 7,4 mg/l
Exposure time: 48 h
Test Type: Immobilization
Method: OECD Test Guideline 202

EC50 (Daphnia magna (Water flea)): > 1 - 10 mg/l
Exposure time: 48 h
Test Type: static test
Method: OECD Test Guideline 202

NOEC (Daphnia magna (Water flea)): 0,27 mg/l
Exposure time: 21 d
Test Type: flow-through test
Method: OECD Test Guideline 211

(Daphnia magna (Water flea)): 7,2 mg/l
Exposure time: 48 h

Toxicity to algae/aquatic plants : EC50 (Desmodesmus subspicatus (green algae)): 27,7 mg/l
Exposure time: 72 h
Test Type: Growth inhibition
Method: OECD Test Guideline 201
GLP: yes

EC50 (Scenedesmus subspicatus): 10 - 100 mg/l
Method: OECD Test Guideline 201

EC50 (Desmodesmus subspicatus (green algae)): > 10 - 100 mg/l
Exposure time: 72 h
Test Type: static test
Method: OECD Test Guideline 201



SANET ALKASTAR 2x5 I

WM 0712472

Order number: 0712472

Version 6.6

Revision Date 24.01.2023

Print Date 05.02.2023

NOEC : 0,95 mg/l
Test Type: Growth inhibition
Method: OECD Test Guideline 201

NOEC (Desmodesmus subspicatus (green algae)): 0,93 mg/l
Exposure time: 72 h
Test Type: static test
Method: OECD Test Guideline 201

Toxicity to microorganisms : EC50 (Pseudomonas putida): > 10 g/l
Exposure time: 16 h
Test Type: Cell multiplication inhibition test
Method: DIN 38412
GLP: yes

EC10 (Pseudomonas putida): > 10 g/l
Test Type: Cell multiplication inhibition test

Toxicity to fish (Chronic toxicity) : NOEC: 1 - 10 mg/l
Species: Leuciscus idus (Golden orfe)

NOEC: 0,14 mg/l
Exposure time: 28 d
Species: Oncorhynchus mykiss (rainbow trout)
Method: OECD Test Guideline 204

Toxicity to daphnia and other aquatic invertebrates (Chronic toxicity) : NOEC: > 0,1 - 1 mg/l
Exposure time: 21 d
Species: Daphnia magna (Water flea)
Method: OECD Test Guideline 211

Toxicity to soil dwelling organisms : NOEC: 750 mg/kg
Exposure time: 96 d
Species: Eisenia fetida (earthworms)
Method: OECD Test Guideline 222

12.2 Persistence and degradability

Product:

Biodegradability : Remarks: The surfactant(s) contained in this preparation complies (comply) with the biodegradability criteria as laid down in Regulation (EC) No. 648/2004 on detergents.

Components:

ALCOHOL:

Biodegradability : Result: Readily biodegradable.
Biodegradation: 97 %
Method: OECD Test Guideline 301

68891-38-3:



SANET ALKASTAR 2x5 I

WM 0712472

Order number: 0712472

Version 6.6

Revision Date 24.01.2023

Print Date 05.02.2023

Biodegradability : Test Type: aerobic
Result: rapidly biodegradable
Biodegradation: > 70 %
Exposure time: 28 d
Method: OECD 301 A

Test Type: anaerobic
Result: Biodegradable
Biodegradation: > 60 %
Exposure time: 41 d

12.3 Bioaccumulative potential

Components:

ALCOHOL:

Bioaccumulation : Concentration: 3,2 mg/l

Partition coefficient: n-
octanol/water : log Pow: -0,32

68891-38-3:

Bioaccumulation : Remarks: Bioaccumulation is unlikely.

12.4 Mobility in soil

No data available

12.5 Results of PBT and vPvB assessment

Components:

68891-38-3:

Assessment : This substance is not considered to be very persistent and very bioaccumulating (vPvB).. This substance is not considered to be persistent, bioaccumulating and toxic (PBT).

12.6 Endocrine disrupting properties

No data available

12.7 Other adverse effects

Product:

Additional ecological information : There is no data available for this product.

SECTION 13: Disposal considerations

13.1 Waste treatment methods

Product : In accordance with local and national regulations.

Contaminated packaging : Empty remaining contents.



SANET ALKASTAR 2x5 I

WM 0712472

Order number: 0712472

Version 6.6

Revision Date 24.01.2023

Print Date 05.02.2023

Empty containers should be taken to an approved waste handling site for recycling or disposal.

SECTION 14: Transport information

14.1 UN number

ADR

Not dangerous goods

IMDG

Not dangerous goods

IATA

Not dangerous goods

14.2 Proper shipping name

Not regulated as a dangerous good

14.3 Transport hazard class

ADR

Not dangerous goods

IMDG

Not dangerous goods

IATA

Not dangerous goods

14.4 Packing group

ADR

Not dangerous goods

IMDG

Not dangerous goods

IATA

Not dangerous goods

14.5 Environmental hazards

ADR

Not dangerous goods

IMDG

Not regulated as a dangerous good

IATA

Not dangerous goods

14.6 Special precautions for user

Remarks : Not classified as dangerous in the meaning of transport regulations.

For personal protection see section 8.

14.7 Transport in bulk according to Annex II of MARPOL 73/78 and the IBC Code

Not applicable for product as supplied.

SECTION 15: Regulatory information

15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture

Regulation (EC) No 649/2012 of the European Parliament and the Council concerning the export and import of dangerous chemicals : Not applicable

REACH - Restrictions on the manufacture, placing on the market and use of certain dangerous substances, preparations : Not applicable



SANET ALKASTAR 2x5 I

WM 0712472

Order number: 0712472

Version 6.6

Revision Date 24.01.2023

Print Date 05.02.2023

and articles (Annex XVII)

Seveso III: Directive 2012/18/EU : Not applicable

of the European Parliament and of
the Council on the control of
major-accident hazards involving
dangerous substances.

TA Luft List (Germany)

- : Total dust: Not applicable
- : Inorganic substances in powdered form: Not applicable
- : Inorganic substances in vapour or gaseous form: Not applicable
- : Organic Substances: : portionClass 1: < 0,01 %
- : Carcinogenic substances: Not applicable
- : Mutagenic: Not applicable
- : Toxic to reproduction: Not applicable

Volatile organic compounds
(VOC) content

- : Directive 2010/75/EU of 24 November 2010 on industrial emissions
(integrated pollution prevention and control)
Update: Percent volatile: 2,43 %
372,01 g/l
VOC content excluding water

Volatile organic compounds
(VOC) content

- : Directive 2010/75/EU of 24 November 2010 on industrial emissions
(integrated pollution prevention and control)
Update: Percent volatile: 2,43 %
25,17 g/l
VOC content valid only for coating materials used on wood surfaces

according to Detergents
Regulation EC 648/2004

- : <5% Anionic surfactants, Perfumes

GISBAU (D)

- : GG 10

15.2 Chemical safety assessment

There is no data available for this product.

SECTION 16: Other information

Full text of H-Statements

- H225 : Highly flammable liquid and vapour.
- H315 : Causes skin irritation.
- H318 : Causes serious eye damage.
- H319 : Causes serious eye irritation.
- H412 : Harmful to aquatic life with long lasting effects.

Full text of other abbreviations

- Aquatic Chronic : Long-term (chronic) aquatic hazard
- Eye Dam. : Serious eye damage
- Eye Irrit. : Eye irritation
- Flam. Liq. : Flammable liquids
- Skin Irrit. : Skin irritation

ADN - European Agreement concerning the International Carriage of Dangerous Goods by Inland Waterways;
ADR - European Agreement concerning the International Carriage of Dangerous Goods by Road; AIIC -
Australian Inventory of Industrial Chemicals; ASTM - American Society for the Testing of Materials; bw - Body



SANET ALKASTAR 2x5 I

WM 0712472

Order number: 0712472

Version 6.6

Revision Date 24.01.2023

Print Date 05.02.2023

weight; CLP - Classification Labelling Packaging Regulation; Regulation (EC) No 1272/2008; CMR - Carcinogen, Mutagen or Reproductive Toxicant; DIN - Standard of the German Institute for Standardisation; DSL - Domestic Substances List (Canada); ECHA - European Chemicals Agency; EC-Number - European Community number; ECx - Concentration associated with x% response; ELx - Loading rate associated with x% response; EmS - Emergency Schedule; ENCS - Existing and New Chemical Substances (Japan); ErCx - Concentration associated with x% growth rate response; GHS - Globally Harmonized System; GLP - Good Laboratory Practice; IARC - International Agency for Research on Cancer; IATA - International Air Transport Association; IBC - International Code for the Construction and Equipment of Ships carrying Dangerous Chemicals in Bulk; IC50 - Half maximal inhibitory concentration; ICAO - International Civil Aviation Organization; IECSC - Inventory of Existing Chemical Substances in China; IMDG - International Maritime Dangerous Goods; IMO - International Maritime Organization; ISHL - Industrial Safety and Health Law (Japan); ISO - International Organisation for Standardization; KECI - Korea Existing Chemicals Inventory; LC50 - Lethal Concentration to 50 % of a test population; LD50 - Lethal Dose to 50% of a test population (Median Lethal Dose); MARPOL - International Convention for the Prevention of Pollution from Ships; n.o.s. - Not Otherwise Specified; NO(A)EC - No Observed (Adverse) Effect Concentration; NO(A)EL - No Observed (Adverse) Effect Level; NOELR - No Observable Effect Loading Rate; NZIoC - New Zealand Inventory of Chemicals; OECD - Organization for Economic Co-operation and Development; OPPTS - Office of Chemical Safety and Pollution Prevention; PBT - Persistent, Bioaccumulative and Toxic substance; PICCS - Philippines Inventory of Chemicals and Chemical Substances; (Q)SAR - (Quantitative) Structure Activity Relationship; REACH - Regulation (EC) No 1907/2006 of the European Parliament and of the Council concerning the Registration, Evaluation, Authorisation and Restriction of Chemicals; RID - Regulations concerning the International Carriage of Dangerous Goods by Rail; SADT - Self-Accelerating Decomposition Temperature; SDS - Safety Data Sheet; SVHC - Substance of Very High Concern; TCSI - Taiwan Chemical Substance Inventory; TECI - Thailand Existing Chemicals Inventory; TRGS - Technical Rule for Hazardous Substances; TSCA - Toxic Substances Control Act (United States); UN - United Nations; vPvB - Very Persistent and Very Bioaccumulative

Further information

Classification of the mixture:

Classification procedure:

Calculation method

The information provided in this Safety Data Sheet is correct to the best of our knowledge, information and belief at the date of its publication. The information given is designed only as a guidance for safe handling, use, processing, storage, transportation, disposal and release and is not to be considered a warranty or quality specification. The information relates only to the specific material designated and may not be valid for such material used in combination with any other materials or in any process, unless specified in the text.

REG_EU / EN

50000000832