

NOWA QUICK-DES 10 X 750 ML CEE

WM 0713161

Order number: 0713161

Version 6.1

Revision Date 08.05.2020

Print Date 24.08.2020

SECTION 1: Identification of the substance/mixture and of the company/undertaking

1.1 Product identifier

Trade name : NOWA QUICK-DES 10 X 750 ML CEE
Identification number : 64390

1.2 Relevant identified uses of the substance or mixture and uses advised against

Use of the Substance/Mixture : Biocidal product
Restricted to professional users.

1.3 Details of the supplier of the safety data sheet

Company : Tana Chemie GmbH
Rheinallee 96
55120 Mainz
Telephone : +49613196403
Telefax : +4961319642414
E-mail address : Produktsicherheit@werner-mertz.com
Responsible/issuing person
Contact person : Product development / product safety

1.4 Emergency telephone number

112
+49(0)6131-19240

SECTION 2: Hazards identification

2.1 Classification of the substance or mixture

Classification (REGULATION (EC) No 1272/2008)

Flammable liquids, Category 2 H225: Highly flammable liquid and vapour.
Eye irritation, Category 2 H319: Causes serious eye irritation.
Specific target organ toxicity - single exposure, Category 3, Central nervous system H336: May cause drowsiness or dizziness.

2.2 Label elements

Labelling (REGULATION (EC) No 1272/2008)

Hazard pictograms :



Signal word : Danger

NOWA QUICK-DES 10 X 750 ML CEE

WM 0713161

Order number: 0713161

Version 6.1

Revision Date 08.05.2020

Print Date 24.08.2020

Hazard statements	:	H225 H319 H336	Highly flammable liquid and vapour. Causes serious eye irritation. May cause drowsiness or dizziness.
Precautionary statements	:	P102 Prevention: P260 P210	Keep out of reach of children. Do not breathe spray. Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.
		Response: P305 + P351 + P338	IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.
		P337 + P313	If eye irritation persists: Get medical advice/attention.
		Disposal: P501	Dispose of contents/ container to an approved waste disposal plant.

Hazardous components which must be listed on the label:
propan-2-ol

Safety data sheet available on request.

2.3 Other hazards

No information available.

SECTION 3: Composition/information on ingredients

3.2 Mixtures

Chemical nature : Aqueous solution of isopropanol
contains
Biocides

Hazardous components

Chemical name	CAS-No. EC-No. Registration number	Classification	Concentration (% w/w)
propan-2-ol	67-63-0 200-661-7 01-2119457558-25	Flam. Liq. 2; H225 Eye Irrit. 2; H319 STOT SE 3; H336	>= 70 - < 80
N-(3-aminopropyl)-N-dodecylpropane-1,3-diamine	2372-82-9 219-145-8 01-2119980592-29	Acute Tox. 3; H301 Skin Corr. 1A; H314 STOT RE 2; H373 Aquatic Acute 1; H400 Aquatic Chronic 1; H410	>= 0,025 - < 0,25

For explanation of abbreviations see section 16.

NOWA QUICK-DES 10 X 750 ML CEE

WM 0713161

Order number: 0713161

Version 6.1

Revision Date 08.05.2020

Print Date 24.08.2020

SECTION 4: First aid measures

4.1 Description of first aid measures

- General advice : Move out of dangerous area.
Consult a physician.
Show this safety data sheet to the doctor in attendance.
- If inhaled : Move to fresh air.
Consult a physician after significant exposure.
- In case of skin contact : Take off contaminated clothing and shoes immediately.
Wash off with soap and plenty of water.
If symptoms persist, call a physician.
- In case of eye contact : Protect unharmed eye.
If easy to do, remove contact lens, if worn.
Rinse immediately with plenty of water, also under the eyelids, for at least 15 minutes.
If eye irritation persists, consult a specialist.
- If swallowed : Clean mouth with water and drink afterwards plenty of water.
Do NOT induce vomiting.
Do not give milk or alcoholic beverages.
Never give anything by mouth to an unconscious person.
Obtain medical attention.

4.2 Most important symptoms and effects, both acute and delayed

- Symptoms : Irritation
- Risks : No information available.

4.3 Indication of any immediate medical attention and special treatment needed

- Treatment : For specialist advice physicians should contact the Poisons Information Service.

SECTION 5: Firefighting measures

5.1 Extinguishing media

- Suitable extinguishing media : Alcohol-resistant foam, Carbon dioxide (CO₂), Dry chemical

5.2 Special hazards arising from the substance or mixture

- Specific hazards during firefighting : Do not allow run-off from fire fighting to enter drains or water courses.
- Hazardous combustion products : No hazardous combustion products are known

NOWA QUICK-DES 10 X 750 ML CEE

WM 0713161

Order number: 0713161

Version 6.1

Revision Date 08.05.2020

Print Date 24.08.2020

5.3 Advice for firefighters

- Special protective equipment for firefighters : In the event of fire, wear self-contained breathing apparatus.
- Further information : Use water spray to cool unopened containers. Collect contaminated fire extinguishing water separately. This must not be discharged into drains. Fire residues and contaminated fire extinguishing water must be disposed of in accordance with local regulations.

SECTION 6: Accidental release measures

6.1 Personal precautions, protective equipment and emergency procedures

- Personal precautions : Use personal protective equipment.
Ensure adequate ventilation.
Remove all sources of ignition.
Evacuate personnel to safe areas.
Beware of vapours accumulating to form explosive concentrations.
Vapours can accumulate in low areas.

6.2 Environmental precautions

- Environmental precautions : Prevent product from entering drains.
Prevent further leakage or spillage if safe to do so.

6.3 Methods and materials for containment and cleaning up

- Methods for cleaning up : Contain spillage, and then collect with non-combustible absorbent material, (e.g. sand, earth, diatomaceous earth, vermiculite) and place in container for disposal according to local / national regulations (see section 13).

6.4 Reference to other sections

- For personal protection see section 8., Treat recovered material as described in the section "Disposal considerations"., Refer to section 15 for specific national regulation.

SECTION 7: Handling and storage

7.1 Precautions for safe handling

- Advice on safe handling : Avoid formation of aerosol. Avoid contact with skin and eyes. For personal protection see section 8. Smoking, eating and drinking should be prohibited in the application area. Take precautionary measures against static discharges. Container may be opened only under exhaust ventilation hood. Open drum carefully as content may be under pressure.
- Advice on protection against fire and explosion : Use explosion-proof equipment. Avoid formation of aerosol. Keep away from sources of ignition - No smoking. Take measures to prevent the build up of electrostatic charge.
- Hygiene measures : Handle in accordance with good industrial hygiene and safety practice. When using do not eat or drink. When using do not smoke. Wash hands before breaks and at the end of workday.

NOWA QUICK-DES 10 X 750 ML CEE

WM 0713161

Order number: 0713161

Version 6.1

Revision Date 08.05.2020

Print Date 24.08.2020

7.2 Conditions for safe storage, including any incompatibilities

Requirements for storage areas and containers : Store in original container. Store in cool place. Containers which are opened must be carefully resealed and kept upright to prevent leakage. Electrical installations / working materials must comply with the technological safety standards. Store at room temperature in the original container.

Other data : No decomposition if stored and applied as directed.

7.3 Specific end use(s)

Specific use(s) : Biocidal product

SECTION 8: Exposure controls/personal protection

8.1 Control parameters

Contains no substances with occupational exposure limit values.

DNEL

propan-2-ol
67-63-0:

: End Use: Workers
Exposure routes: Skin contact
Potential health effects: Long-term systemic effects
Value: 888 mg/kg

End Use: Workers
Exposure routes: Inhalation
Potential health effects: Long-term systemic effects
Value: 500 mg/m³

End Use: Consumers
Exposure routes: Skin contact
Potential health effects: Long-term systemic effects
Value: 319 mg/kg

End Use: Consumers
Exposure routes: Ingestion
Potential health effects: Long-term systemic effects
Value: 26 mg/kg

End Use: Consumers
Exposure routes: Inhalation
Potential health effects: Long-term systemic effects
Value: 89 mg/m³

N-(3-aminopropyl)-N-
dodecylpropane-1,3-diamine
2372-82-9:

: End Use: Workers
Exposure routes: Dermal
Potential health effects: Long-term systemic effects
Value: 0,91 mg/kg

End Use: Consumers
Exposure routes: Dermal

NOWA QUICK-DES 10 X 750 ML CEE

WM 0713161

Order number: 0713161

Version 6.1

Revision Date 08.05.2020

Print Date 24.08.2020

Value: 0,54 mg/kg

End Use: Consumers
Exposure routes: Inhalation
Potential health effects: Long-term systemic effects
Value: 0,7 mg/m³

End Use: Consumers
Exposure routes: Oral
Value: 0,2 mg/kg

End Use: Workers
Exposure routes: Inhalation
Potential health effects: Long-term systemic effects
Value: 2,35 mg/m³

PNEC

propan-2-ol
67-63-0:

: Fresh water
Value: 140,9 mg/l

Marine water
Value: 140,9 mg/l

Fresh water sediment
Value: 552 mg/kg

Marine sediment
Value: 552 mg/kg

Soil
Value: 28 mg/kg

intermittent release
Value: 140,9 mg/l

STP
Value: 2251 mg/l

Oral
Value: 160 mg/kg

N-(3-aminopropyl)-N-
dodecylpropane-1,3-diamine
2372-82-9:

: Fresh water
Value: 0,001 mg/l

Soil
Value: 45,34 mg/kg

Marine sediment
Value: 0,85 mg/kg

Fresh water sediment
Value: 8,5 mg/kg

STP
Value: 1,33 mg/l

NOWA QUICK-DES 10 X 750 ML CEE

WM 0713161

Order number: 0713161

Version 6.1

Revision Date 08.05.2020

Print Date 24.08.2020

8.2 Exposure controls

Personal protective equipment

Eye protection : If splashes are likely to occur, wear:
Tightly fitting safety goggles

Hand protection

Material : For prolonged or repeated contact use protective gloves.
It is suggested the usage of chemical resistant gloves made of butyl rubber or nitrile rubber category III according to EN 374-1: 2003 (0,4 mm).
As alternative, a different type of gloves might be used if, accordingly to the recommendations of the producer, guarantee the same level of protection.

Remarks : Take note of the information given by the producer concerning permeability and break through times, and of special workplace conditions (mechanical strain, duration of contact).

Skin and body protection : not required under normal use

Respiratory protection : Not required; except in case of aerosol formation.
Recommended Filter type:
ABEK-P3-filter

Environmental exposure controls

General advice : Prevent product from entering drains.
Prevent further leakage or spillage if safe to do so.

SECTION 9: Physical and chemical properties

9.1 Information on basic physical and chemical properties

Appearance : liquid

Colour : colourless

Odour : alcohol-like

Odour Threshold : No data available

pH : ca. 9,5, at20 °C

Melting point/range : No data available

Boiling point/boiling range : No information available.

Flash point : ca. 18 °C

Evaporation rate : No data available

Flammability (solid, gas) : No data available

NOWA QUICK-DES 10 X 750 ML CEE

WM 0713161

Order number: 0713161

Version 6.1

Revision Date 08.05.2020

Print Date 24.08.2020

Flammability (liquids) : No data available
Burning rate : No data available
Lower explosion limit : No data available
Upper explosion limit : No data available
Vapour pressure : No data available
Relative vapour density : No data available
Relative density : No data available
Density : ca. 0,860 g/cm³ at 20 °C

Water solubility : soluble

Solubility in other solvents : No data available

Partition coefficient: n-octanol/water : No data available

Ignition temperature : No data available

Thermal decomposition : No data available

Viscosity, dynamic : No data available

Viscosity, kinematic : No data available

Explosive properties : No data available

Oxidizing properties : No data available

9.2 Other information

none

SECTION 10: Stability and reactivity

10.1 Reactivity

Stable under recommended storage conditions., No dangerous reaction known under conditions of normal use.

10.2 Chemical stability

No decomposition if stored and applied as directed.

10.3 Possibility of hazardous reactions

Hazardous reactions : Vapours may form explosive mixture with air.

Stable under recommended storage conditions., No decomposition if used as directed.

10.4 Conditions to avoid

Conditions to avoid : Heat, flames and sparks.

10.5 Incompatible materials

Materials to avoid : No data available

10.6 Hazardous decomposition products

NOWA QUICK-DES 10 X 750 ML CEE

WM 0713161

Order number: 0713161

Version 6.1

Revision Date 08.05.2020

Print Date 24.08.2020

Hazardous decomposition products : No hazardous decomposition products are known.
Other information : No hazardous decomposition products are known.

SECTION 11: Toxicological information

11.1 Information on toxicological effects

Product

Skin corrosion/irritation : May cause skin irritation in susceptible persons.

Serious eye damage/eye irritation : Vapours may cause irritation to the eyes, respiratory system and the skin.
Causes serious eye irritation.

Respiratory or skin sensitisation : No data available

Germ cell mutagenicity : Not Rated

Carcinogenicity : Not Rated

Reproductive toxicity : Not Rated

STOT - single exposure : The substance or mixture is not classified as specific target organ toxicant, single exposure.

STOT - repeated exposure : The substance or mixture is not classified as specific target organ toxicant, repeated exposure.

Aspiration toxicity : Not Rated

Further information : Symptoms of overexposure may be headache, dizziness, tiredness, nausea and vomiting., Concentrations substantially above the TLV value may cause narcotic effects., Solvents may degrease the skin.

Components:

propan-2-ol

67-63-0:

Acute oral toxicity : LD50 Oral Rat: 5.840 mg/kg
Method: OECD Test Guideline 401

LD50 Oral Rat: 4.570 mg/kg

Acute inhalation toxicity : LC50 Rat, female: 47,5 mg/l
Exposure time: 8 h
Method: OECD Test Guideline 403

LC50 Rat: 72,6 mg/l

NOWA QUICK-DES 10 X 750 ML CEE

WM 0713161

Order number: 0713161

Version 6.1

Revision Date 08.05.2020

Print Date 24.08.2020

Exposure time: 4 h

LC50 Mouse: 27,2 mg/l
Exposure time: 4 h

LC50 Rat: 25 mg/l
Exposure time: 6 h
Method: OECD Test Guideline 403

LC50 Rat: 30 mg/l
Exposure time: 4 h

LC50 Rat: 10000 ppm
Exposure time: 6 h

Acute dermal toxicity : LD50 Rabbit: 12.800 mg/kg
Method: OECD Test Guideline 402

LD50 Dermal Rabbit: 12.870 mg/kg
Method: OECD Test Guideline 402

LD50 Dermal Rabbit: 13.900 mg/kg
Method: OECD Test Guideline 402

LD50 Dermal Rabbit: 13.400 mg/kg

Skin corrosion/irritation : Species: Rabbit
Result: No skin irritation

Serious eye damage/eye irritation : Species: Rabbit
Result: irritating

Respiratory or skin sensitisation : Test Method: Buehler Test
Species: Guinea pig
Result: Does not cause skin sensitisation.

Germ cell mutagenicity

Genotoxicity in vitro : Type: Ames test
Test species: Salmonella typhimurium
with and without metabolic activation
Result: negative

N-(3-aminopropyl)-N-dodecylpropane-1,3-diamine
2372-82-9:

Acute oral toxicity : LD50 Rat, female: 243,6 mg/kg
Method: OECD Test Guideline 401
GLP: yes

NOWA QUICK-DES 10 X 750 ML CEE

WM 0713161

Order number: 0713161

Version 6.1

Revision Date 08.05.2020

Print Date 24.08.2020

- LD50 Rat, male: 280 mg/kg
Method: OECD Test Guideline 401
GLP: yes
- Acute dermal toxicity : LD50 Rat: > 600 mg/kg
Method: OECD Test Guideline 402
- Skin corrosion/irritation : Species: Rabbit
Exposure time: 3 min
Result: Causes severe burns.
Method: OECD Test Guideline 404
- Respiratory or skin sensitisation : Test Method: Buehler Test
Species: Guinea pig
Result: Did not cause sensitisation on laboratory animals.
Method: OECD Test Guideline 406
- Germ cell mutagenicity
- Genotoxicity in vitro : Test species: Chinese hamster cells
Metabolic activation
Result: negative
Method: OECD Test Guideline 476
- : Type: Chromosome aberration test in vitro
Test species: Chinese hamster cells
Metabolic activation
Result: negative
Method: OECD Test Guideline 473
- : Type: Ames test
Test species: Salmonella typhimurium
Metabolic activation
Result: negative
Method: OECD Test Guideline 471
- Repeated dose toxicity : Rat: NOAEL: 9 mg/kg
- Application Route: Oral
Exposure time: 90 d
Method: OECD Test Guideline 408
GLP: yes
- Dog: NOAEL: 20 mg/kg
- Application Route: Dermal
Exposure time: 90 d
Method: OECD Test Guideline 409
GLP: yes
- Rat: NOAEL: 15 mg/kg
- Application Route: Dermal

NOWA QUICK-DES 10 X 750 ML CEE

WM 0713161

Order number: 0713161

Version 6.1

Revision Date 08.05.2020

Print Date 24.08.2020

Exposure time: 90 d
GLP: yes

SECTION 12: Ecological information

12.1 Toxicity

Components:

propan-2-ol
67-63-0:

- Toxicity to fish : LC50 (Lepomis macrochirus (Bluegill sunfish)): 1.400 mg/l
Exposure time: 96 h
- LC50 (Pimephales promelas (fathead minnow)): 9.640 mg/l
Exposure time: 96 h
- LC50 (Leuciscus idus (Golden orfe)): > 100 mg/l
Exposure time: 48 h
Test Type: static test
GLP: no
- Toxicity to daphnia and other aquatic invertebrates : EC50 (Daphnia magna (Water flea)): 13.299 mg/l
Exposure time: 48 h
- EC50 (Daphnia magna (Water flea)): 9.714 mg/l
Exposure time: 24 h
- EC50 (Daphnia magna (Water flea)): > 100 mg/l
Exposure time: 48 h
Test Type: static test
GLP: no
- (Daphnia (water flea)): > 10.000 mg/l
Method: OECD Test Guideline 202
- NOEC (Daphnia magna (Water flea)): 30 mg/l
Exposure time: 21 d
- EC50 (Daphnia magna (Water flea)): 10.000 mg/l
Exposure time: 48 h
- Toxicity to algae : IC50 (Desmodesmus subspicatus (green algae)): > 1.000 mg/l
Exposure time: 72 h
Test Type: Growth inhibition
- EC50 (Pseudokirchneriella subcapitata (microalgae)): > 100 mg/l
Exposure time: 72 h
Test Type: static test
GLP: no
- ErC50 (Pseudokirchneriella subcapitata (green algae)): > 1.000 mg/l
Exposure time: 72 h
- EC50 (Scenedesmus subspicatus): > 100 mg/l
Exposure time: 72 h
Test Type: static test

NOWA QUICK-DES 10 X 750 ML CEE

WM 0713161

Order number: 0713161

Version 6.1

Revision Date 08.05.2020

Print Date 24.08.2020

Toxicity to bacteria : EC50 (*Aliivibrio fischeri*): 17.700 mg/l
Exposure time: 5 min
GLP:

EC10 (*Pseudomonas putida*): 5.175 mg/l
Exposure time: 18 h
Method: DIN 38412
GLP:

N-(3-aminopropyl)-N-dodecylpropane-1,3-diamine 2372-82-9:

Toxicity to fish : LC50 (*Danio rerio* (zebra fish)): 0,44 mg/l
Exposure time: 96 h
Method: OECD Test Guideline 203

LC50 (*Oncorhynchus mykiss* (rainbow trout)): 0,68 mg/l
Exposure time: 96 h
Method: OECD Test Guideline 203
GLP: yes

LC50 (*Lepomis macrochirus* (Bluegill sunfish)): 0,45 mg/l
Exposure time: 96 h
Analytical monitoring: yes
GLP: yes

Toxicity to daphnia and other aquatic invertebrates : EC0 (*Daphnia magna* (Water flea)): 0,3 mg/l
Exposure time: 24 h
Method: OECD Test Guideline 202

EC50 (*Daphnia magna* (Water flea)): 0,073 mg/l
Exposure time: 48 h
Test Type: Immobilization
Analytical monitoring: yes
GLP: yes

NOEC (*Daphnia magna* (Water flea)): 0,024 mg/l
Exposure time: 21 d
Test Type: Reproduction Test
Analytical monitoring: yes
Method: OECD Test Guideline 211
GLP: yes

Toxicity to algae : ErC50 (*Pseudokirchneriella subcapitata* (green algae)): 0,054 mg/l
Exposure time: 96 h
Test Type: Growth inhibition
GLP: yes

ErC10 (*Desmodesmus subspicatus* (green algae)): 0,012 mg/l
Exposure time: 72 h
Test Type: Growth inhibition
Analytical monitoring: yes
Method: OECD Test Guideline 201
GLP: yes

(*Desmodesmus subspicatus* (green algae)): 0,0069 mg/l
Exposure time: 72 h
Test Type: Growth inhibition

NOWA QUICK-DES 10 X 750 ML CEE

WM 0713161

Order number: 0713161

Version 6.1

Revision Date 08.05.2020

Print Date 24.08.2020

Method: OECD Test Guideline 201

M-Factor (Short-term (acute)
aquatic hazard) : 10

Toxicity to bacteria : EC50 (Bacteria): 0,8 mg/l
Method: DIN 38412
GLP:

EC50 (activated sludge): 18 mg/l
Exposure time: 3 h
Test Type: Respiration inhibition
Method: OECD Test Guideline 209
GLP: yes

M-Factor (Long-term (chronic)
aquatic hazard) : 1

12.2 Persistence and degradability

Components:

propan-2-ol 67-63-0:

Biodegradability : Result: rapidly biodegradable
Biodegradation: 95 %
Exposure time: 21 d
Method: OECD 301 E

Inoculum: activated sludge
Result: rapidly biodegradable
Biodegradation: 53 %
Exposure time: 5 d

Result: rapidly biodegradable
Biodegradation: > 70 %
Exposure time: 10 d
GLP: no

Biodegradation: 99,9 %
Method: see user defined free text

Chemical Oxygen Demand
(COD) : 2,32 g/kg

ThOD : 2,40 g/g

N-(3-aminopropyl)-N-dodecylpropane-1,3-diamine 2372-82-9:

Biodegradability : Result: Readily biodegradable.
Biodegradation: > 90 %
Exposure time: 28 d
Method: OECD Test Guideline 301

Test Type: Zahn-Wellens Test
Biodegradation: 91 %
Exposure time: 28 d
Method: OECD Test Guideline 302B

NOWA QUICK-DES 10 X 750 ML CEE

WM 0713161

Order number: 0713161

Version 6.1

Revision Date 08.05.2020

Print Date 24.08.2020

Test Type: see user defined free text
Result: rapidly biodegradable
Biodegradation: 79 %
Exposure time: 28 d
Method: OECD 301 D
GLP: yes

Biodegradation: 96 %
Exposure time: 12 - 15 d
Method: OECD Test Guideline 303A

Chemical Oxygen Demand (COD) : 2.875 mg/g
Remarks: see user defined free text

Dissolved organic carbon (DOC) : 721 mg/g
Remarks: see user defined free text

12.3 Bioaccumulative potential

Components:

propan-2-ol

67-63-0:

Bioaccumulation : Bioconcentration factor (BCF): 3

Remarks: No bioaccumulation is to be expected (log Pow <= 4).

Partition coefficient: n-octanol/water : log Pow: 0,05

N-(3-aminopropyl)-N-dodecylpropane-1,3-diamine

2372-82-9:

Partition coefficient: n-octanol/water : log Pow: 4,46
Remarks: see user defined free text

12.4 Mobility in soil

Components:

propan-2-ol

67-63-0:

Distribution among environmental compartments : Koc: 25
Remarks: Highly mobile in soils

N-(3-aminopropyl)-N-dodecylpropane-1,3-diamine

2372-82-9:

Mobility : Remarks: After release, adsorbs onto soil.

12.5 Results of PBT and vPvB assessment

Components:

propan-2-ol

67-63-0:

Assessment : This substance is not considered to be very persistent and very bioaccumulating (vPvB).. This substance is not considered to be persistent, bioaccumulating and toxic (PBT)..

N-(3-aminopropyl)-N-dodecylpropane-1,3-diamine

NOWA QUICK-DES 10 X 750 ML CEE

WM 0713161

Order number: 0713161

Version 6.1

Revision Date 08.05.2020

Print Date 24.08.2020

2372-82-9:

Assessment

: This substance is not considered to be very persistent and very bioaccumulating (vPvB).. This substance is not considered to be persistent, bioaccumulating and toxic (PBT)..

12.6 Other adverse effects

Product:

Additional ecological information : There is no data available for this product.

Components:

LAURYLAMINE DIPROPYLENEDIAMINE:

Additional ecological information : An environmental hazard cannot be excluded in the event of unprofessional handling or disposal., Very toxic to aquatic life with long lasting effects.

SECTION 13: Disposal considerations

13.1 Waste treatment methods

Product : Do not dispose of waste into sewer.
Do not contaminate ponds, waterways or ditches with chemical or used container.
Offer surplus and non-recyclable solutions to a licensed disposal company.

Contaminated packaging : Empty remaining contents.
Dispose of as unused product.
Do not re-use empty containers.
Do not burn, or use a cutting torch on, the empty drum.

SECTION 14: Transport information

14.1 UN number

ADR : 1219
IMDG : 1219
IATA : 1219

14.2 Proper shipping name

ADR : ISOPROPANOL
IMDG : ISOPROPANOL
IATA : Isopropanol Not permitted for transport

14.3 Transport hazard class

ADR : 3
IMDG : 3
IATA : 3

14.4 Packing group

ADR
Classification Code : F1
Packaging group : II
Hazard Identification Number : 33
Labels : 3

NOWA QUICK-DES 10 X 750 ML CEE

WM 0713161

Order number: 0713161

Version 6.1

Revision Date 08.05.2020

Print Date 24.08.2020

Tunnel restriction code : (D/E)
IMDG
Packaging group : II
Labels : 3
EmS Number : F-E, S-D
IATA
(Cargo) : Isopropanol Not permitted for transport
Packaging group : II
Labels : 3

14.5 Environmental hazards

ADR
Environmentally hazardous : no

IMDG
Marine pollutant : no
IATA
Environmentally hazardous : no

14.6 Special precautions for user

The transport classification(s) provided herein are for informational purposes only, and solely based upon the properties of the unpackaged material as it is described within this Safety Data Sheet. Transportation classifications may vary by mode of transportation, package sizes, and variations in regional or country regulations.

For personal protection see section 8.

14.7 Transport in bulk according to Annex II of MARPOL 73/78 and the IBC Code

Not applicable for product as supplied.

SECTION 15: Regulatory information

15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture

Regulation (EC) No 649/2012 of the European Parliament and the Council concerning the export and import of dangerous chemicals : Not applicable

REACH - Restrictions on the manufacture, placing on the market and use of certain dangerous substances, preparations and articles (Annex XVII) : See Annex XVII to Regulation (EC) no 1907/2006 for Conditions of restriction

Seveso III: Directive 2012/18/EU of the European Parliament and of the Council on the control of major-accident hazards involving dangerous substances.

		Quantity 1	Quantity 2
P5c	FLAMMABLE LIQUIDS	5.000 000067	50.000 000067

TA Luft List (Germany) : Total dust: Not applicable
: Inorganic substances in powdered form: Not applicable
: Inorganic substances in vapour or gaseous form: Not applicable
: Organic Substances: : portionClass 1: 0,09 %
: Carcinogenic substances: Not applicable
: Mutagenic: Not applicable
: Toxic to reproduction: Not applicable

Volatile organic compounds (VOC) content : Directive 2010/75/EU of 24 November 2010 on industrial emissions (integrated pollution prevention and control)

NOWA QUICK-DES 10 X 750 ML CEE

WM 0713161

Order number: 0713161

Version 6.1

Revision Date 08.05.2020

Print Date 24.08.2020

Update: Percent volatile: 70 %
809,81 g/l
VOC content excluding water

Volatile organic compounds (VOC) content : Directive 2010/75/EU of 24 November 2010 on industrial emissions (integrated pollution prevention and control)
Update: Percent volatile: 70 %
601,31 g/l
VOC content valid only for coating materials used on wood surfaces

according to Detergents Regulation EC 648/2004 : disinfectants, LAURYLAMINE DIPROPYLENEDIAMINE

GISBAU (D) : GD 30

15.2 Chemical safety assessment

There is no data available for this product.

SECTION 16: Other information

Full text of H-Statements

H225	Highly flammable liquid and vapour.
H301	Toxic if swallowed.
H314	Causes severe skin burns and eye damage.
H319	Causes serious eye irritation.
H336	May cause drowsiness or dizziness.
H373	May cause damage to organs through prolonged or repeated exposure.
H400	Very toxic to aquatic life.
H410	Very toxic to aquatic life with long lasting effects.

Further information

Items where changes have been made to the previous version are highlighted in the body of this document by two vertical lines.

Classification procedure:	H225	On basis of test data.
	H319	Calculation method
	H336	Calculation method

ADN - European Agreement concerning the International Carriage of Dangerous Goods by Inland Waterways; ADR - European Agreement concerning the International Carriage of Dangerous Goods by Road; AICS - Australian Inventory of Chemical Substances; ASTM - American Society for the Testing of Materials; bw - Body weight; CLP - Classification Labelling Packaging Regulation; Regulation (EC) No 1272/2008; CMR - Carcinogen, Mutagen or Reproductive Toxicant; DIN - Standard of the German Institute for Standardisation; DSL - Domestic Substances List (Canada); ECHA - European Chemicals Agency; EC-Number - European Community number; ECx - Concentration associated with x% response; ELx - Loading rate associated with x% response; EmS - Emergency Schedule; ENCS - Existing and New Chemical Substances (Japan); ErCx - Concentration associated with x% growth rate response; GHS - Globally Harmonized System; GLP - Good Laboratory Practice; IARC - International Agency for Research on Cancer; IATA - International Air Transport Association; IBC - International Code for the Construction and Equipment of Ships carrying Dangerous Chemicals in Bulk; IC50 - Half maximal inhibitory concentration; ICAO - International Civil Aviation Organization; IECSC - Inventory of Existing Chemical Substances in China; IMDG - International Maritime Dangerous Goods;

SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006



NOWA QUICK-DES 10 X 750 ML CEE

WM 0713161

Order number: 0713161

Version 6.1

Revision Date 08.05.2020

Print Date 24.08.2020

IMO - International Maritime Organization; ISHL - Industrial Safety and Health Law (Japan); ISO - International Organisation for Standardization; KECI - Korea Existing Chemicals Inventory; LC50 - Lethal Concentration to 50 % of a test population; LD50 - Lethal Dose to 50% of a test population (Median Lethal Dose); MARPOL - International Convention for the Prevention of Pollution from Ships; n.o.s. - Not Otherwise Specified; NO(A)EC - No Observed (Adverse) Effect Concentration; NO(A)EL - No Observed (Adverse) Effect Level; NOELR - No Observable Effect Loading Rate; NZIoC - New Zealand Inventory of Chemicals; OECD - Organization for Economic Co-operation and Development; OPPTS - Office of Chemical Safety and Pollution Prevention; PBT - Persistent, Bioaccumulative and Toxic substance; PICCS - Philippines Inventory of Chemicals and Chemical Substances; (Q)SAR - (Quantitative) Structure Activity Relationship; REACH - Regulation (EC) No 1907/2006 of the European Parliament and of the Council concerning the Registration, Evaluation, Authorisation and Restriction of Chemicals; RID - Regulations concerning the International Carriage of Dangerous Goods by Rail; SADT - Self-Accelerating Decomposition Temperature; SDS - Safety Data Sheet; SVHC - Substance of Very High Concern; TCSI - Taiwan Chemical Substance Inventory; TRGS - Technical Rule for Hazardous Substances; TSCA - Toxic Substances Control Act (United States); UN - United Nations; vPvB - Very Persistent and Very Bioaccumulative

The information provided in this Safety Data Sheet is correct to the best of our knowledge, information and belief at the date of its publication. The information given is designed only as a guidance for safe handling, use, processing, storage, transportation, disposal and release and is not to be considered a warranty or quality specification. The information relates only to the specific material designated and may not be valid for such material used in combination with any other materials or in any process, unless specified in the text.

500000001246