

GRILL EXPRESS 750 ml D/GB

WM 0712727

Order number: 0712727

Version 8.0

Revision Date 08.05.2020

Print Date 24.08.2020

SECTION 1: Identification of the substance/mixture and of the company/undertaking

1.1 Product identifier

Trade name : GRILL EXPRESS 750 ml D/GB
Identification number : 61979, 64358

1.2 Relevant identified uses of the substance or mixture and uses advised against

Use of the Substance/Mixture : Cleaning agent
Restricted to professional users.

1.3 Details of the supplier of the safety data sheet

Company : Tana Chemie GmbH
Rheinallee 96
55120 Mainz
Telephone : +49613196403
Telefax : +4961319642414
E-mail address : Produktsicherheit@werner-mertz.com
Responsible/issuing person
Contact person : Product development / product safety

1.4 Emergency telephone number

112
+49(0)6131-19240

SECTION 2: Hazards identification

2.1 Classification of the substance or mixture

Classification (REGULATION (EC) No 1272/2008)

Corrosive to metals, Category 1 H290: May be corrosive to metals.

Skin corrosion, Category 1A H314: Causes severe skin burns and eye damage.

2.2 Label elements

Labelling (REGULATION (EC) No 1272/2008)

Hazard pictograms :



Signal word : Danger

Hazard statements : H290 May be corrosive to metals.
H314 Causes severe skin burns and eye damage.

Precautionary statements : P102 Keep out of reach of children.

Prevention:

GRILL EXPRESS 750 ml D/GB

WM 0712727

Order number: 0712727

Version 8.0

Revision Date 08.05.2020

Print Date 24.08.2020

P260 Do not breathe spray.
P280 Wear protective gloves/ protective clothing/ eye protection/ face protection.

Response:
P303 + P361 + P353 IF ON SKIN (or hair): Take off immediately all contaminated clothing. Rinse skin with water.
P304 + P340 + P310 IF INHALED: Remove person to fresh air and keep comfortable for breathing. Immediately call a POISON CENTER/doctor.
P305 + P351 + P338 IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. Immediately call a POISON CENTER/doctor.

P310
Disposal:
P501 Dispose of contents/ container to an approved waste disposal plant.

Hazardous components which must be listed on the label:
sodium hydroxide

Safety data sheet available on request.

2.3 Other hazards

No information available.

SECTION 3: Composition/information on ingredients

3.2 Mixtures

Chemical nature : Aqueous surfactant solution.

Hazardous components

Chemical name	CAS-No. EC-No. Registration number	Classification	Concentration (% w/w)
sodium hydroxide	1310-73-2 215-185-5 01-2119457892-27-XXXX	Met. Corr. 1; H290 Skin Corr. 1A; H314 SCL ≥ 5 % 1A; H314 2 - < 5 % 1B; H314 0,5 - < 2 % 2; H315 0,5 - < 2 % 2; H319	≥ 5 - < 10
sodium p-cumenesulphonate	15763-76-5 239-854-6 01-2119489411-37	Eye Dam. 2; H319	≥ 2 - < 5
Substances with a workplace exposure limit :			
1-(2-butoxy-1-methylethoxy)propan-2-ol	29911-28-2 249-951-5 01-2119451543-42		≥ 2 - < 5

GRILL EXPRESS 750 ml D/GB

WM 0712727

Order number: 0712727

Version 8.0

Revision Date 08.05.2020

Print Date 24.08.2020

(2-methoxymethylethoxy)propanol	34590-94-8 252-104-2 01-2119450011-60		>= 2 - < 5
---------------------------------	---	--	------------

For explanation of abbreviations see section 16.

SECTION 4: First aid measures

4.1 Description of first aid measures

- General advice : Move out of dangerous area.
Consult a physician.
Show this safety data sheet to the doctor in attendance.
- If inhaled : Move to fresh air.
If symptoms persist, call a physician.
- In case of skin contact : Take off contaminated clothing and shoes immediately.
Wash off with soap and plenty of water.
Immediate medical treatment is necessary as untreated wounds from corrosion of the skin heal slowly and with difficulty.
- In case of eye contact : Small amounts splashed into eyes can cause irreversible tissue damage and blindness.
Protect unharmed eye.
Continue rinsing eyes during transport to hospital.
- If swallowed : Clean mouth with water and drink afterwards plenty of water.
Do NOT induce vomiting.
Do not give milk or alcoholic beverages.
Never give anything by mouth to an unconscious person.
Take victim immediately to hospital.

4.2 Most important symptoms and effects, both acute and delayed

- Symptoms : corrosive effects
- Risks : No information available.

4.3 Indication of any immediate medical attention and special treatment needed

- Treatment : For specialist advice physicians should contact the Poisons Information Service.

SECTION 5: Firefighting measures

5.1 Extinguishing media

- Suitable extinguishing media : Use extinguishing measures that are appropriate to local circumstances and the surrounding environment.

5.2 Special hazards arising from the substance or mixture

GRILL EXPRESS 750 ml D/GB

WM 0712727

Order number: 0712727

Version 8.0

Revision Date 08.05.2020

Print Date 24.08.2020

Specific hazards during firefighting : Do not allow run-off from fire fighting to enter drains or water courses.

Hazardous combustion products :
No hazardous combustion products are known

5.3 Advice for firefighters

Special protective equipment for firefighters : In the event of fire, wear self-contained breathing apparatus.

Further information : Collect contaminated fire extinguishing water separately. This must not be discharged into drains. Fire residues and contaminated fire extinguishing water must be disposed of in accordance with local regulations.

SECTION 6: Accidental release measures

6.1 Personal precautions, protective equipment and emergency procedures

Personal precautions : Use personal protective equipment.
Ensure adequate ventilation.
Evacuate personnel to safe areas.

6.2 Environmental precautions

Environmental precautions : Do not flush into surface water or sanitary sewer system.

6.3 Methods and materials for containment and cleaning up

Methods for cleaning up : Neutralise with acid.
Soak up with inert absorbent material (e.g. sand, silica gel, acid binder, universal binder, sawdust).
Keep in suitable, closed containers for disposal.

6.4 Reference to other sections

For personal protection see section 8., Treat recovered material as described in the section "Disposal considerations"., Refer to section 15 for specific national regulation.

SECTION 7: Handling and storage

7.1 Precautions for safe handling

Advice on safe handling : Avoid formation of aerosol. Avoid contact with skin and eyes. For personal protection see section 8. Smoking, eating and drinking should be prohibited in the application area. To avoid spills during handling keep bottle on a metal tray.

Advice on protection against fire and explosion : Normal measures for preventive fire protection.

Hygiene measures : Handle in accordance with good industrial hygiene and safety practice. When using do not eat or drink. When using do not smoke. Wash hands before breaks and at the end of workday.

GRILL EXPRESS 750 ml D/GB

WM 0712727

Order number: 0712727

Version 8.0

Revision Date 08.05.2020

Print Date 24.08.2020

7.2 Conditions for safe storage, including any incompatibilities

Requirements for storage areas and containers : Store in original container. Keep container tightly closed in a dry and well-ventilated place. Containers which are opened must be carefully resealed and kept upright to prevent leakage. Store at room temperature in the original container.

Other data : No decomposition if stored and applied as directed.

7.3 Specific end use(s)

Specific use(s) : Cleaning agent

SECTION 8: Exposure controls/personal protection

8.1 Control parameters

Components	CAS-No.	Value type (Form of exposure)	Control parameters	Update	Basis
(2-methoxymethyllethoxy)propanol	34590-94-8	TWA	50 ppm 308 mg/m ³	2000-06-16	2000/39/EC
Further information	: skin: Identifies the possibility of significant uptake through the skinIndicative				
(2-methoxymethyllethoxy)propanol	34590-94-8	TWA	50 ppm 308 mg/m ³		
Further information	: H: Dermal absorption possible				
(2-methoxymethyllethoxy)propanol	34590-94-8		100 ppm		
Further information	: H: Dermal absorption possible				
(2-methoxymethyllethoxy)propanol	34590-94-8	STEL	150 ppm		
Further information	: H: Dermal absorption possible				
(2-methoxymethyllethoxy)propanol	34590-94-8		100 ppm		
Further information	: REL: Recommended exposure limit				
(2-methoxymethyllethoxy)propanol	34590-94-8	STEL	150 ppm 900 mg/m ³		
(2-methoxymethyllethoxy)propanol	34590-94-8	STEL	50 ppm 310 mg/m ³		

GRILL EXPRESS 750 ml D/GB

WM 0712727

Order number: 0712727

Version 8.0

Revision Date 08.05.2020

Print Date 24.08.2020

DNEL

sodium hydroxide
1310-73-2:

: End Use: Workers
Exposure routes: Inhalation
Potential health effects: Long-term systemic effects, Long-term local effects
Value: 1,5 mg/m³

End Use: Workers
Exposure routes: Inhalation
Potential health effects: Short-term exposure, Local effects, Systemic effects
Value: 3 mg/m³

End Use: Consumers
Exposure routes: Inhalation
Potential health effects: Long-term local effects, Long-term systemic effects
Value: 0,6 mg/m³

End Use: Consumers
Exposure routes: Inhalation
Potential health effects: Short-term exposure, Local effects, Systemic effects
Value: 1,2 mg/m³

End Use: Consumers
Exposure routes: Ingestion
Potential health effects: Long-term local effects, Long-term systemic effects
Value: 25 mg/m³

sodium p-cumenesulphonate
15763-76-5:

: End Use: Workers
Exposure routes: Skin contact
Potential health effects: Long-term systemic effects
Value: 7,6 mg/kg

End Use: Workers
Exposure routes: Inhalation
Potential health effects: Long-term systemic effects
Value: 53,6 mg/m³

End Use: Consumers
Exposure routes: Skin contact
Potential health effects: Long-term systemic effects
Value: 3,8 mg/kg

End Use: Consumers
Exposure routes: Inhalation
Potential health effects: Long-term systemic effects
Value: 13,2 mg/m³

End Use: Consumers
Exposure routes: Ingestion
Potential health effects: Long-term systemic effects

GRILL EXPRESS 750 ml D/GB

WM 0712727

Order number: 0712727

Version 8.0

Revision Date 08.05.2020

Print Date 24.08.2020

**1-(2-butoxy-1-methylethoxy)propan-2-ol
29911-28-2:**

Value: 3,8 mg/kg bw/day

End Use: Workers
Exposure routes: Skin contact
Potential health effects: Long-term systemic effects
Value: 136,25 mg/kg bw/day

End Use: Workers
Exposure routes: Inhalation
Potential health effects: Long-term systemic effects
Value: 26,9 mg/m³

End Use: Workers
Exposure routes: Skin contact
Potential health effects: Long-term local effects
Value: 0,096 mg/cm²

End Use: Consumers
Exposure routes: Skin contact
Potential health effects: Long-term systemic effects
Value: 68,1 mg/kg bw/day

End Use: Consumers
Exposure routes: Inhalation
Potential health effects: Long-term systemic effects
Value: 6,6 mg/m³

End Use: Consumers
Exposure routes: Inhalation
Potential health effects: Long-term local effects
Value: 0,048 mg/cm²

: End Use: Workers
Exposure routes: Inhalation
Potential health effects: Long-term systemic effects
Value: 189 mg/m³

End Use: Workers
Exposure routes: Dermal
Potential health effects: Long-term systemic effects
Value: 134 mg/kg

End Use: Consumers
Exposure routes: Inhalation
Potential health effects: Long-term systemic effects
Value: 56 mg/m³

End Use: Consumers
Exposure routes: Dermal
Potential health effects: Long-term systemic effects
Value: 80 mg/kg

End Use: Consumers
Exposure routes: Oral
Potential health effects: Long-term systemic effects
Value: 16 mg/kg

(2-

: End Use: Workers

GRILL EXPRESS 750 ml D/GB

WM 0712727

Order number: 0712727

Version 8.0

Revision Date 08.05.2020

Print Date 24.08.2020

**methoxymethylethoxy)propan
ol**
34590-94-8:

Exposure routes: Skin contact
Potential health effects: Long-term systemic effects
Value: 65 mg/kg

End Use: Workers
Exposure routes: Inhalation
Potential health effects: Long-term systemic effects
Value: 310 mg/m³

End Use: Consumers
Exposure routes: Skin contact
Potential health effects: Long-term systemic effects
Value: 15 mg/kg

End Use: Consumers
Exposure routes: Ingestion
Potential health effects: Long-term systemic effects
Value: 1,67 mg/kg

End Use: Consumers
Exposure routes: Inhalation
Potential health effects: Long-term systemic effects
Value: 37,2 mg/m³

End Use: Workers
Exposure routes: Inhalation
Potential health effects: Long-term systemic effects
Value: 308 mg/m³

End Use: Workers
Exposure routes: Skin contact
Potential health effects: Long-term systemic effects
Value: 283 mg/kg

End Use: Consumers
Exposure routes: Skin contact
Potential health effects: Long-term systemic effects
Value: 121 mg/kg

End Use: Consumers
Exposure routes: Ingestion
Potential health effects: Long-term systemic effects
Value: 36 mg/kg

PNEC

sodium p-cumenesulphonate
15763-76-5:

: Fresh water
Value: 0,23 mg/l

STP
Value: 100 mg/l

intermittent release
Value: 2,3 mg/l

Marine water
Value: 0,023 mg/l

GRILL EXPRESS 750 ml D/GB

WM 0712727

Order number: 0712727

Version 8.0

Revision Date 08.05.2020

Print Date 24.08.2020

	Fresh water sediment Value: 0,862 mg/kg
	Marine sediment Value: 0,0862 mg/kg
	Soil Value: 0,037 mg/kg
1-(2-butoxy-1-methylethoxy)propan-2-ol 29911-28-2:	: Fresh water Value: 0,519 mg/l
	Marine water Value: 0,0519 mg/l
	Fresh water sediment Value: 2,96 mg/kg
	Marine sediment Value: 0,296 mg/kg
	Soil Value: 0,287 mg/kg
	STP Value: 100 mg/l
	intermittent release Value: 2,96 mg/kg
	intermittent release Value: 5,19 mg/l
(2-methoxymethylethoxy)propan ol 34590-94-8:	: Fresh water Value: 19 mg/l
	Marine water Value: 1,9 mg/l
	Fresh water sediment Value: 70,2 mg/kg
	Marine sediment Value: 7,02 mg/kg
	Soil Value: 2,74 mg/kg
	Water Value: 190 mg/l
	STP Value: 4168 mg/l

8.2 Exposure controls

Personal protective equipment

GRILL EXPRESS 750 ml D/GB

WM 0712727

Order number: 0712727

Version 8.0

Revision Date 08.05.2020

Print Date 24.08.2020

- Eye protection : Tightly fitting safety goggles
- Hand protection
- Material : Chemical resistant gloves made of butyl rubber or nitrile rubber category III according to EN 374.
- Remarks : Take note of the information given by the producer concerning permeability and break through times, and of special workplace conditions (mechanical strain, duration of contact).
- Skin and body protection : Choose body protection according to the amount and concentration of the dangerous substance at the work place.
Remove and wash contaminated clothing before re-use.
- Respiratory protection : Not required; except in case of aerosol formation.
Recommended Filter type:
ABEK-P3-filter

Environmental exposure controls

- General advice : Do not flush into surface water or sanitary sewer system.

SECTION 9: Physical and chemical properties

9.1 Information on basic physical and chemical properties

- Appearance : liquid
- Colour : tan
- Odour : characteristic
- Odour Threshold : No data available
- pH : ca. 13, at20 °C
- Melting point/range : No data available
- Boiling point/boiling range : No information available.
- Flash point : Not applicable
- Evaporation rate : No data available
- Flammability (solid, gas) : No data available
- Flammability (liquids) : No data available
- Burning rate : No data available
- Lower explosion limit : No data available
- Upper explosion limit : No data available
- Vapour pressure : No data available
- Relative vapour density : No data available
- Relative density : No data available

GRILL EXPRESS 750 ml D/GB

WM 0712727

Order number: 0712727

Version 8.0

Revision Date 08.05.2020

Print Date 24.08.2020

Density	: ca. 1,074 g/cm ³ at 20 °C
Water solubility	: soluble
Solubility in other solvents	: No data available
Partition coefficient: n-octanol/water	: No data available
Ignition temperature	: No data available
Thermal decomposition	: No data available
Viscosity, dynamic	: No data available
Viscosity, kinematic	: No data available
Explosive properties	: No data available
Oxidizing properties	: No data available

9.2 Other information

none

SECTION 10: Stability and reactivity

10.1 Reactivity

Stable under recommended storage conditions., No dangerous reaction known under conditions of normal use.

10.2 Chemical stability

No decomposition if stored and applied as directed.

10.3 Possibility of hazardous reactions

Hazardous reactions : Stable under recommended storage conditions., No decomposition if used as directed.

10.4 Conditions to avoid

Conditions to avoid : No data available

10.5 Incompatible materials

Materials to avoid : No data available

10.6 Hazardous decomposition products

Hazardous decomposition products : No hazardous decomposition products are known.
Other information : No hazardous decomposition products are known.

SECTION 11: Toxicological information

11.1 Information on toxicological effects

Product

Skin corrosion/irritation : Extremely corrosive and destructive to tissue.

GRILL EXPRESS 750 ml D/GB

WM 0712727

Order number: 0712727

Version 8.0

Revision Date 08.05.2020

Print Date 24.08.2020

Serious eye damage/eye irritation	: May cause irreversible eye damage.
Respiratory or skin sensitisation	: No data available
Germ cell mutagenicity	: Not Rated
Carcinogenicity	: Not Rated
Reproductive toxicity	: Not Rated
STOT - single exposure	: The substance or mixture is not classified as specific target organ toxicant, single exposure.
STOT - repeated exposure	: The substance or mixture is not classified as specific target organ toxicant, repeated exposure.
Aspiration toxicity	: Not Rated
Further information	: No data available

Components:

sodium hydroxide

1310-73-2:

Acute oral toxicity	: LD50 Oral Rat: 2.000 mg/kg
Skin corrosion/irritation	: Result: Corrosive
Serious eye damage/eye irritation	: Result: Corrosive

sodium p-cumenesulphonate

15763-76-5:

Acute oral toxicity	: LD50 Oral Rat: > 2.000 mg/kg Method: OECD Test Guideline 401
Acute inhalation toxicity	: LC50 Rat: 5 mg/l Exposure time: 232 min
Acute dermal toxicity	: LD50 Dermal Rabbit: > 2.000 mg/kg
Skin corrosion/irritation	: Species: Rabbit Result: Mild skin irritation Method: OECD Test Guideline 404 Based on available data, the classification criteria are not met.
Serious eye damage/eye irritation	: Species: Rabbit

GRILL EXPRESS 750 ml D/GB

WM 0712727

Order number: 0712727

Version 8.0

Revision Date 08.05.2020

Print Date 24.08.2020

irritation	Result: Moderate eye irritation Method: OECD Test Guideline 405 Causes serious eye irritation.
Respiratory or skin sensitisation	: Test Method: Buehler Test Species: Guinea pig Result: Did not cause sensitisation on laboratory animals. Method: OECD Test Guideline 406
Germ cell mutagenicity	
Genotoxicity in vitro	: Result: negative
Genotoxicity in vivo	: Result: negative
Carcinogenicity - Assessment	: Animal testing did not show any carcinogenic effects.
Teratogenicity	: Species: Rat Application Route: Oral 3.000 mg/kg 3.000 mg/kg
Repeated dose toxicity	: Rat: NOAEL: 763 mg/kg Application Route: Oral Target Organs: Cardio-vascular system Mouse: NOAEL: 440 mg/kg LOAEL: 1.300 mg/kg Application Route: Dermal Method: OECD Test Guideline 411 Target Organs: Skin

1-(2-butoxy-1-methylethoxy)propan-2-ol

29911-28-2:

Acute oral toxicity	: LD50 Rat: 3.700 mg/kg
Acute inhalation toxicity	: LC50 Rat: > 2,04 mg/l Exposure time: 4 h
Acute dermal toxicity	: LD50 Rat: > 2.000 mg/kg

(2-methoxymethylethoxy)propanol

34590-94-8:

Acute oral toxicity	: LD50 Dog: 7.500 mg/kg LD50 Rat: 5.130 mg/kg LD50 Rat: 5.135 mg/kg
---------------------	---

GRILL EXPRESS 750 ml D/GB

WM 0712727

Order number: 0712727

Version 8.0

Revision Date 08.05.2020

Print Date 24.08.2020

Acute inhalation toxicity	: LC50 Rat: 55 - 60 mg/l Exposure time: 4 h
	LC50 Rat: 3,35 mg/l Exposure time: 7 h
Acute dermal toxicity	: LD50 Dermal Rabbit: 19.000 mg/kg
	LD50 Dermal Rat: 9.500 mg/kg
	LD50 Rabbit: 9.510 mg/kg
	LD50 Rabbit: 14.000 mg/kg
Skin corrosion/irritation	: No skin irritation
Serious eye damage/eye irritation	: Result: No eye irritation
Respiratory or skin sensitisation	: Result: Does not cause skin sensitisation.

SECTION 12: Ecological information

12.1 Toxicity

Components:

sodium hydroxide

1310-73-2:

Toxicity to fish	: LC50 (Fish): 33 - 189 mg/l Exposure time: 96 h
	LC50 (Gambusia affinis (Mosquito fish)): 125 mg/l Exposure time: 96 h
	LC50 (Poecilia reticulata (guppy)): 76 mg/l Exposure time: 24 h
Toxicity to daphnia and other aquatic invertebrates	: EC50 (Daphnia (water flea)): 40,4 mg/l
	EC50 (Daphnia magna (Water flea)): 76 mg/l Exposure time: 24 h
Toxicity to bacteria	: EC50 (Photobacterium phosphoreum): 22 mg/l Exposure time: 15 min

sodium p-cumenesulphonate

15763-76-5:

Toxicity to fish	: LC50 (Cyprinus carpio (Carp)): > 100 mg/l Exposure time: 96 h Method: OECD Test Guideline 203
------------------	---

GRILL EXPRESS 750 ml D/GB

WM 0712727

Order number: 0712727

Version 8.0

Revision Date 08.05.2020

Print Date 24.08.2020

	LC50 (<i>Oncorhynchus mykiss</i> (rainbow trout)): > 100 mg/l Exposure time: 96 h Test Type: static test
Toxicity to daphnia and other aquatic invertebrates	: EC50 (<i>Daphnia magna</i> (Water flea)): > 100 mg/l Exposure time: 48 h Test Type: static test Method: OECD Test Guideline 202
Toxicity to algae	: EC50 (<i>Desmodesmus subspicatus</i> (green algae)): > 100 mg/l Exposure time: 72 h Method: OECD Test Guideline 201
	EC50 (<i>Pseudokirchneriella subcapitata</i> (green algae)): > 100 mg/l Exposure time: 96 h Test Type: static test
Toxicity to bacteria	: EC10 (activated sludge): > 1.000 mg/l Exposure time: 3 h Test Type: Respiration inhibition Method: OECD Test Guideline 209

1-(2-butoxy-1-methylethoxy)propan-2-ol 29911-28-2:

Toxicity to fish	: LC50 (<i>Poecilia reticulata</i> (guppy)): 841 mg/l Exposure time: 96 h Test Type: static test
Toxicity to daphnia and other aquatic invertebrates	: EC50 (<i>Daphnia magna</i> (Water flea)): > 1.000 mg/l Exposure time: 48 h Test Type: static test

(2-methoxymethylethoxy)propanol 34590-94-8:

Toxicity to fish	: (<i>Pimephales promelas</i> (fathead minnow)): > 10.000 mg/l Exposure time: 96 h Test Type: static test
	(<i>Poecilia reticulata</i> (guppy)): > 1.000 mg/l Exposure time: 96 h Test Type: static test
Toxicity to daphnia and other aquatic invertebrates	: EC50 (<i>Daphnia magna</i> (Water flea)): 1.919 mg/l Exposure time: 48 h Test Type: static test
	EC50 (<i>Crangon crangon</i> (shrimp)): > 1.000 mg/l Exposure time: 96 h Test Type: semi-static test
	NOEC (<i>Daphnia magna</i> (Water flea)): > 0,5 mg/l Exposure time: 22 d
Toxicity to algae	: (<i>Pseudokirchneriella subcapitata</i> (microalgae)): > 969 mg/l Exposure time: 96 h Method: OECD Test Guideline 201
	(<i>Selenastrum capricornutum</i>): 1.000 mg/l

GRILL EXPRESS 750 ml D/GB

WM 0712727

Order number: 0712727

Version 8.0

Revision Date 08.05.2020

Print Date 24.08.2020

	Exposure time: 72 h
	EC50 (Skeletonema costatum (marine diatom)): 6.999 mg/l Exposure time: 72 h
Toxicity to bacteria	: EC10 (Pseudomonas putida): 4.168 mg/l Exposure time: 18 h Test Type: Growth inhibition
	EC50 (No data available): > 100 mg/l
Toxicity to daphnia and other aquatic invertebrates (Chronic toxicity)	: NOEC: 12 mg/l Species: Daphnia magna (Water flea)
	NOEC: > 0,5 mg/l Exposure time: 22 d Species: Daphnia magna (Water flea)
	Lowest Observed Effect Concentration: > 0,5 mg/l Exposure time: 22 d Species: Daphnia magna (Water flea)

12.2 Persistence and degradability

Product:

Biodegradability : Remarks: The surfactant(s) contained in this preparation complies (comply) with the biodegradability criteria as laid down in Regulation (EC) No. 648/2004 on detergents.

Components:

sodium hydroxide

1310-73-2:

Biodegradability : Remarks: The methods for determining the biological degradability are not applicable to inorganic substances.

sodium p-cumenesulphonate

15763-76-5:

Biodegradability : Test Type: aerobic
Result: Readily biodegradable.
Biodegradation: > 60 %
Exposure time: 28 d
Method: OECD 301 B

1-(2-butoxy-1-methylethoxy)propan-2-ol

29911-28-2:

Biodegradability : Biodegradation: 91 %
Exposure time: 28 d
Method: OECD 301 E

Biodegradation: 95 %
Exposure time: 21 d
Method: OECD 301 A

(2-methoxymethylethoxy)propanol

34590-94-8:

GRILL EXPRESS 750 ml D/GB

WM 0712727

Order number: 0712727

Version 8.0

Revision Date 08.05.2020

Print Date 24.08.2020

Biodegradability : Result: Readily biodegradable.
Biodegradation: > 70 %
Exposure time: 28 d
Method: OECD 301 E

Biodegradation: 75 %
Exposure time: 28 d
Method: OECD 301 F

Biodegradation: 93 %
Exposure time: 13 d
Method: OECD 302 B

12.3 Bioaccumulative potential

Components:

sodium hydroxide

1310-73-2:

Bioaccumulation : Species: Fish
Remarks: No bioaccumulation is to be expected (log Pow <= 4).

sodium p-cumenesulphonate

15763-76-5:

Bioaccumulation : Remarks: Bioaccumulation is unlikely.

1-(2-butoxy-1-methylethoxy)propan-2-ol

29911-28-2:

Partition coefficient: n-
octanol/water : log Pow: 1,523

(2-methoxymethylethoxy)propanol

34590-94-8:

Bioaccumulation : Remarks: No bioaccumulation is to be expected (log Pow <= 4).

Partition coefficient: n-
octanol/water : log Pow: 1,01

12.4 Mobility in soil

Components:

sodium p-cumenesulphonate

15763-76-5:

Stability in soil : Remarks: Not expected to adsorb on soil.

1-(2-butoxy-1-methylethoxy)propan-2-ol

29911-28-2:

Distribution among
environmental compartments : Koc: 10 - 20

12.5 Results of PBT and vPvB assessment

Components:

(2-methoxymethylethoxy)propanol

34590-94-8:

Assessment : This substance is not considered to be very persistent and very bioaccumulating (vPvB).. This substance is not considered to be persistent, bioaccumulating and toxic (PBT)..

GRILL EXPRESS 750 ml D/GB

WM 0712727

Order number: 0712727

Version 8.0

Revision Date 08.05.2020

Print Date 24.08.2020

12.6 Other adverse effects

Product:

Additional ecological information : There is no data available for this product.

SECTION 13: Disposal considerations

13.1 Waste treatment methods

- Product : Do not dispose of waste into sewer.
Do not contaminate ponds, waterways or ditches with chemical or used container.
Offer surplus and non-recyclable solutions to a licensed disposal company.
- Contaminated packaging : Empty remaining contents.
Dispose of as unused product.
Do not re-use empty containers.

SECTION 14: Transport information

14.1 UN number

- ADR : 3266
IMDG : 3266
IATA : 3266

14.2 Proper shipping name

- ADR : CORROSIVE LIQUID, BASIC, INORGANIC, N.O.S.
(sodium hydroxide)
- IMDG : CORROSIVE LIQUID, BASIC, INORGANIC, N.O.S.
(sodium hydroxide)
- IATA : Corrosive liquid, basic, inorganic, n.o.s. Not permitted for transport

14.3 Transport hazard class

- ADR : 8
IMDG : 8
IATA : 8

14.4 Packing group

- ADR
Classification Code : C5
Packaging group : III
Hazard Identification Number : 80
Labels : 8
Tunnel restriction code : (E)
- IMDG
Packaging group : III
Labels : 8
EmS Number : F-A, S-B
- IATA
(Cargo) : Corrosive liquid, basic, inorganic, n.o.s. Not permitted for transport
Packaging group : III
Labels : 8

GRILL EXPRESS 750 ml D/GB

WM 0712727

Order number: 0712727

Version 8.0

Revision Date 08.05.2020

Print Date 24.08.2020

14.5 Environmental hazards

ADR

Environmentally hazardous : no

IMDG

Marine pollutant : no

IATA

Environmentally hazardous : no

14.6 Special precautions for user

The transport classification(s) provided herein are for informational purposes only, and solely based upon the properties of the unpackaged material as it is described within this Safety Data Sheet. Transportation classifications may vary by mode of transportation, package sizes, and variations in regional or country regulations.

For personal protection see section 8.

14.7 Transport in bulk according to Annex II of MARPOL 73/78 and the IBC Code

Not applicable for product as supplied.

SECTION 15: Regulatory information

15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture

Regulation (EC) No 649/2012 of the European Parliament and the Council concerning the export and import of dangerous chemicals : Not applicable

REACH - Restrictions on the manufacture, placing on the market and use of certain dangerous substances, preparations and articles (Annex XVII) : Not applicable

Seveso III: Directive 2012/18/EU : Not applicable

of the European Parliament and of the Council on the control of major-accident hazards involving dangerous substances.

TA Luft List (Germany) : Total dust: Not applicable
: Inorganic substances in powdered form: Not applicable
: Inorganic substances in vapour or gaseous form: Not applicable
: Organic Substances: Not applicable
: Carcinogenic substances: Not applicable
: Mutagenic: Not applicable
: Toxic to reproduction: Not applicable

Volatile organic compounds (VOC) content : Directive 2010/75/EU of 24 November 2010 on industrial emissions (integrated pollution prevention and control)
Update: Percent volatile: 5,25 %
591,66 g/l
VOC content excluding water

Volatile organic compounds (VOC) content : Directive 2010/75/EU of 24 November 2010 on industrial emissions (integrated pollution prevention and control)
Update: Percent volatile: 5,25 %
56,28 g/l

GRILL EXPRESS 750 ml D/GB

WM 0712727

Order number: 0712727

Version 8.0

Revision Date 08.05.2020

Print Date 24.08.2020

VOC content valid only for coating materials used on wood surfaces

according to Detergents
Regulation EC 648/2004 : <5% Anionic surfactants, soap

GISBAU (D) : GG 80

15.2 Chemical safety assessment

There is no data available for this product.

SECTION 16: Other information

Full text of H-Statements

H290 May be corrosive to metals.
H314 Causes severe skin burns and eye damage.
H319 Causes serious eye irritation.

Further information

Items where changes have been made to the previous version are highlighted in the body of this document by two vertical lines.

Classification procedure:	H290	Calculation method
	H314	Calculation method

ADN - European Agreement concerning the International Carriage of Dangerous Goods by Inland Waterways; ADR - European Agreement concerning the International Carriage of Dangerous Goods by Road; AICS - Australian Inventory of Chemical Substances; ASTM - American Society for the Testing of Materials; bw - Body weight; CLP - Classification Labelling Packaging Regulation; Regulation (EC) No 1272/2008; CMR - Carcinogen, Mutagen or Reproductive Toxicant; DIN - Standard of the German Institute for Standardisation; DSL - Domestic Substances List (Canada); ECHA - European Chemicals Agency; EC-Number - European Community number; ECx - Concentration associated with x% response; ELx - Loading rate associated with x% response; EmS - Emergency Schedule; ENCS - Existing and New Chemical Substances (Japan); ErCx - Concentration associated with x% growth rate response; GHS - Globally Harmonized System; GLP - Good Laboratory Practice; IARC - International Agency for Research on Cancer; IATA - International Air Transport Association; IBC - International Code for the Construction and Equipment of Ships carrying Dangerous Chemicals in Bulk; IC50 - Half maximal inhibitory concentration; ICAO - International Civil Aviation Organization; IECSC - Inventory of Existing Chemical Substances in China; IMDG - International Maritime Dangerous Goods; IMO - International Maritime Organization; ISHL - Industrial Safety and Health Law (Japan); ISO - International Organisation for Standardization; KECl - Korea Existing Chemicals Inventory; LC50 - Lethal Concentration to 50 % of a test population; LD50 - Lethal Dose to 50% of a test population (Median Lethal Dose); MARPOL - International Convention for the Prevention of Pollution from Ships; n.o.s. - Not Otherwise Specified; NO(A)EC - No Observed (Adverse) Effect Concentration; NO(A)EL - No Observed (Adverse) Effect Level; NOELR - No Observable Effect Loading Rate; NZIoC - New Zealand Inventory of Chemicals; OECD - Organization for Economic Co-operation and Development; OPPTS - Office of Chemical Safety and Pollution Prevention; PBT - Persistent, Bioaccumulative and Toxic substance; PICCS - Philippines Inventory of Chemicals and Chemical Substances; (Q)SAR - (Quantitative) Structure Activity Relationship; REACH - Regulation (EC) No 1907/2006 of the European Parliament and of the Council concerning the Registration, Evaluation, Authorisation and Restriction of Chemicals; RID - Regulations concerning the International Carriage of Dangerous Goods by Rail; SADT - Self-Accelerating Decomposition Temperature; SDS - Safety Data Sheet; SVHC - Substance of Very High Concern; TCSI - Taiwan Chemical Substance Inventory; TRGS - Technical Rule for Hazardous Substances; TSCA - Toxic Substances Control Act (United States); UN - United Nations; vPvB - Very Persistent and Very Bioaccumulative



GRILL EXPRESS 750 ml D/GB

WM 0712727

Order number: 0712727

Version 8.0

Revision Date 08.05.2020

Print Date 24.08.2020

The information provided in this Safety Data Sheet is correct to the best of our knowledge, information and belief at the date of its publication. The information given is designed only as a guidance for safe handling, use, processing, storage, transportation, disposal and release and is not to be considered a warranty or quality specification. The information relates only to the specific material designated and may not be valid for such material used in combination with any other materials or in any process, unless specified in the text.

500000001702